

## CH-4/CI-4 HDEO ADDITIVE PACKAGE T32065

### • Introduction

T32065 is the mainstream diesel engine oil additive package product. It provides high quality and stable performance for heavy duty diesel engine. The product contains optimized combination of dispersant, antioxidant, excellent detergent, and has excellent wear resistance, effective protection of the engine and prolong the oil service life.

### • Recommended Treat Rate

Performance Level	Treat Rate (wt%)
CI-4	12.0
CH-4	10.0

### • Specifications

Item	Typical Value	Test Method
Appearance	Red Brown Viscous Liquid	Visual
Kinematic Viscosity (100°C), mm <sup>2</sup> /s	Report	GB/T 265
Flash Point (COC), °C	> 110	GB/T 3536
Total Base Number, mgKOH/g	110	SH/T 0251
Nitrogen, wt%	0.75	ASTM D5185 (ICP)
Zinc, wt%	1.20	ASTM D5185 (ICP)
Calcium, wt%	3.75	ASTM D5185 (ICP)
Phosphorus, wt%	1.0	ASTM D5185 (ICP)

### • Package, Handle & Storage

1. Packed in 200L metal drum, IBC-Tank or made to order.
2. Long term storage temperature should not exceed 45°C.
3. Handle & blending temperature should not exceed 65°C.
4. Not dangerous chemical, store in dry & clean warehouse.